

H.C.B-L1012 W/ L1014 FRONT CRANKSHAFT OIL SEAL INSTALLATION KIT
FORD | JAGUAR | LAND ROVER



* Crankshaft Front Oil Seal Tool (303-679A) Designed to remove the front crankshaft oil seal. Simply remove the front pulley, and use this tool to wind out the seal. The new seal will have an internal seal lip protector. This should be left

Rating: Not Rated Yet
Price:

Sales price:
Discount:

[Ask a question about this product](#)
Manufacturer: [HCB Specialty Tools](#)

Description

[View product details](#)

[View product details](#)

[View product details](#)

[View product details](#)

[View product details](#)

[View product details](#)

[View product details](#)

[View product details](#)

[View product details](#)

1. Remove the front oil seal.

2. Remove the front oil seal from the crankshaft.

3. Remove the front oil seal from the crankshaft.

4. Remove the front oil seal from the crankshaft.

5. Remove the front oil seal from the crankshaft.

6. Remove the front oil seal from the crankshaft.

7. Remove the front oil seal from the crankshaft.

8. Remove the front oil seal from the crankshaft.

9. Remove the front oil seal from the crankshaft.

10. Remove the front oil seal from the crankshaft.

11. Remove the front oil seal from the crankshaft.

12. Remove the front oil seal from the crankshaft.

13. Remove the front oil seal from the crankshaft.